

Fully Optimized for Telemetry



BR1 Mini Core

Mini Core



High Level of Security Compliance


Designed with strict security compliance in mind, we've tailor-made the device to exclude Wi-Fi & GPS functionality, making it great for networks that require a highly secure connection.



Government




Military



Public Safety & Emergency Services



Finance



Full GPIO functionality

Seamlessly integrate telemetry devices into your network with the BR1 Mini Core's built-in I/O functionality.

Power through AC/DC

Now available for purchase with DC cables, we aim to make it easy for our users to sync up all their devices with zero hassle.

Certified safe for work

With UL and Class 1 Division 2 certifications, among many others, the BR1 Mini Core is ready to handle demanding setups.





Specifications

WAN Interface	1x 10/100/1000M Ethernet ¹ 1x Embedded Cellular Modem with Redundant SIM Slots	Antenna Connectors	2x SMA Cellular Antenna Connectors
LAN Interface	2x 10/100/1000M Ethernet	Power Input	Power Port: 10V – 30V DC AC Adapter: AC Input 100V–240V / DC Output 12V
SpeedFusion features	Hot Failover ¹ / Smoothing ¹ / Bandwidth Bonding ^{1,2}	Power Consumption	10W (nominal), 16W (max.)
Number of PepVPN SpeedFusion Peers	2 / 5 ³	Dimension	5.0 x 4.2 x 1.4 inches / 125.7 x 107 x 35 mm
Feature	GPIO	Weight	0.95 pounds / 430 grams
Router Throughput	300Mbps	Operating Temperature	-40° – 149°F / -40° – 65°C
PepVPN Throughput (No Encryption)	80Mbps	Humidity	15% – 95% (non-condensing)
PepVPN Throughput (256-bit AES)	20 Mbps / 60Mbps ³	Certifications	FCC, CE, RoHS UL+CUL (62368-1) UL 121201 (Class I and Division 2)
Recommended Users	1-60	Package Content	1x BR1 Mini Core 2x LTE Antennas (ACW-235) 1x 12V 2A 4pin Power Supply (ACW-632)
Cellular Data Rate⁴ (Downlink/Uplink)	CAT-7: 300 Mbps/150 Mbps CAT-4: 150 Mbps/50 Mbps	SIM Options	Nano-SIM (4FF) Peplink eSIM BYO eSIM (2 profiles) ²
		Warranty	1-Year Limited Warranty

¹ Available with a feature pack add-on license or PrimeCare / PrimeCare+ subscription.

² Available with Firmware 8.4.0 or above.

³ Requires a PrimeCare subscription, complimentary for the first year.

⁴ Maximum theoretical data rate.

Specifications are subject to change without notice.

Ordering Information

Product Code	Regions	LTE Bands	3G Bands
MAX-BR1-MINI-LTEA-US-T-M-PRM Embedded Modem(s): 1x CAT-7	North America* *US Carrier Certifications: AT&T, FirstNet, T-Mobile, Verizon	B2, B4, B5, B7, B12, B13, B14, B25, B26, B41, B42, B43, B48, B66, B71	WCDMA/HSPA+/DC-HSPA+: B2, B4, B5
MAX-BR1-MINI-LTE-US-T-M-PRM Embedded Modem(s): 1x CAT-4	North America* *US Carrier Certifications: AT&T, FirstNet, T-Mobile, Verizon	B2, B4, B5, B12, B13, B14, B66, B71	WCDMA/HSPA+/DC-HSPA+: B2, B5
MAX-BR1-MINI-LTE-E-T-M-PRM Embedded Modem(s): 1x CAT-4	APAC, EMEA	B1, B3, B5, B7, B8, B20, B38, B40, B41	WCDMA/HSPA+/DC-HSPA+: B1, B5, B8
MAX-BR1-MINI-LTE-MX-T-M-PRM Embedded Modem(s): 1x CAT-4	APAC, Latin America, Australia	B1, B2, B3, B4, B5, B7, B8, B28, B40	WCDMA/HSPA+/DC-HSPA+: B1, B2, B5, B8

Featured Add-on

Product Code	Description
PRM-A-1Y / PCP-A-1Y	PrimeCare A / PrimeCare+ A (1-Year)
PRM-A-2Y / PCP-A-2Y	PrimeCare A / PrimeCare+ A (2-Year)
PRM-A-4Y / PCP-A-4Y	PrimeCare A / PrimeCare+ A (4-Year)
MAX-BR1-MINI-LC-FP	Feature pack for BR1 Mini Core enables Ethernet WAN, Hot Failover, WAN Smoothing
ANT-MB-20G-S-B-6	3-in-1 Cellular Antenna System with GPS Receiver (Black)
ANT-MB-20G-S-W-6	3-in-1 Cellular Antenna System with GPS Receiver (White)
ACW-634	10ft DC Power Cable
ACW-DIN-BR1-MINI	DIN Rail Mount